



# DD1 SERIES CONNECTORS

0.5mm Pitch Stroke Connector conforming to USB2.0 Standard

## ORDERING INFORMATION

• **Receptacle**      **DD1 - R 030 H A 1**

Series \_\_\_\_\_

Receptacle \_\_\_\_\_

No. of Contacts: 30 pos. \_\_\_\_\_

Connector Type: H - Hold Down \_\_\_\_\_

Plating Specification \_\_\_\_\_

    A - Contact Area: Au Plating: 0.1µm min.  
    Terminal Area: Au Flash Plating

Modification Code \_\_\_\_\_

## ORDERING INFORMATION

• **Cradle**      **DD1 - B 030 H A 1**

Series \_\_\_\_\_

B - Cradle \_\_\_\_\_

No. of Contacts: 30 pos. \_\_\_\_\_

Connector Type: H - Hold Down \_\_\_\_\_

    V - 75 degree Tilted Type

Plating Specification \_\_\_\_\_

    A - Contact Area: Au Plating: 0.1µm min.  
    Terminal Area: Au Flash Plating

Modification Code \_\_\_\_\_

## ORDERING INFORMATION

• **Plug**      **DD1 - P 030 M A 1**

Series \_\_\_\_\_

P - Plug \_\_\_\_\_

No. of Contacts: 30 pos. \_\_\_\_\_

Connector Type: M - Soldered to Cable \_\_\_\_\_

Plating Specification \_\_\_\_\_

    A - Contact Area: Au Plating: 0.1µm min.  
    Terminal Area: Au Flash Plating

Modification Code \_\_\_\_\_

• Please consult JAE for verification of product availability.

Dimensions in mm (inches).