

DD2 SERIES CONNECTORS

0.5mm Pitch Stroke Connector conforming to USB2.0 Standard

ORDERING INFORMATION

• **Receptacle** **DD2 - R 040 H P 2**

Series _____

Receptacle _____

No. of Contacts: 40 pos. _____

Connector Type: H - Hold Down _____

Plating Specification _____

 P - Contact Area: Au Plating: 0.1µm min.
 Terminal Area: Au Flash Plating

Modification Code _____

ORDERING INFORMATION

• **Cradle** **DD2 - B 040 H A 2**

Series _____

B - Cradle _____

No. of Contacts: 40 pos. _____

Connector Type: H - Hold Down _____

 V - 75 degree Tilted Type

Plating Specification _____

 A - Contact Area: Au Plating: 0.1µm min.
 Terminal Area: Au Flash Plating

Modification Code _____

ORDERING INFORMATION

• **Plug** **DD2 - P 040 M A 1**

Series _____

P - Plug _____

No. of Contacts: 40 pos. _____

Connector Type: M - Soldered to Cable _____

Plating Specification _____

 A - Contact Area: Au Plating: 0.1µm min.
 Terminal Area: Au Flash Plating

Modification Code _____

• Please consult JAE for verification of product availability.

Dimensions in mm (inches).